

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 December 2000 (21.12.2000)

PCT

(10) International Publication Number
WO 00/76806 A1

(51) International Patent Classification⁷: **B60P 1/38**

(21) International Application Number: **PCT/GB00/02277**

(22) International Filing Date: **13 June 2000 (13.06.2000)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
9913952.9 **15 June 1999 (15.06.1999)** **GB**

(71) Applicant (for all designated States except US): **MULTIDRIVE LIMITED [GB/GB];** Thirsk Industrial Park, York Road, Thirsk, Yorkshire YO7 3BX (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BROWN, David, John, Bowes** [—/GB]; Ravenshorpe Manor, Boltby, Thirsk, Yorkshire YO7 2DX (GB).

(74) Agent: **GODWIN, Edgar, James; Marks & Clerk, 57-60** Lincoln's Inn Fields, London WC2A 3LS (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **LOAD CARRYING BODY**



(57) Abstract: A floor constituted by a flexible belt (23), resting on the upper surface of a loadbearing base, has one end connected to a headboard (17) and the other end connected to a winch (28). A cable (33) has one end connected to the headboard and the other end connected to the winch. A guide system for the cable including a compensating mechanism (36, 56, 57) which varies the path of the cable during rotation of the winch, so as to compensate for a difference between the belt diameter and the cable diameter on the winch, the difference varying as the belt is wound and unwound.

WO 00/76806 A1